

◆UPSS-A3シリーズ(100V)

負荷機器の消費電力(W)			100	200	400	600	800	1000	1200	1500	1800	2000	2200	2400	2600	3000	3200	3600	4000	
入力電圧	容量	型番	バックアップ時間(分) ※周囲温度25℃																	
100V	1kVA	UPSS-10A3-010	105	52.5	27	16.5	12	-	-	-	-	-	-	-	-	-	-	-	-	-
		UPSS-10A3-030	237	123.5	58	40.5	31	-	-	-	-	-	-	-	-	-	-	-	-	-
		UPSS-10A3-060	501	277.5	138.5	90.5	65.5	-	-	-	-	-	-	-	-	-	-	-	-	-
	1.5kVA	UPSS-15A3-010	125.5	68	35.5	23.5	16	12.5	10.5	-	-	-	-	-	-	-	-	-	-	-
		UPSS-15A3-030	356	208	103.5	65.5	48	41.5	33.5	-	-	-	-	-	-	-	-	-	-	-
		UPSS-15A3-060	721	416	211.5	136	94.5	76.5	61	-	-	-	-	-	-	-	-	-	-	-
	2kVA	UPSS-20A3-008	162.5	92	43	31	22	15.5	13	9.5	-	-	-	-	-	-	-	-	-	-
		UPSS-20A3-030	432.5	269.5	132.5	87	62	48.5	43	31.5	-	-	-	-	-	-	-	-	-	-
		UPSS-20A3-060	879	549.5	266	175	127.5	95.5	78.5	58	-	-	-	-	-	-	-	-	-	-
	3kVA	UPSS-30A3-008	254	170.5	81.5	48	35.5	29	22.5	15.5	12.5	11.5	9	8	-	-	-	-	-	-
		UPSS-30A3-030	384.5	282.5	160	101	73	58.5	49.5	40.5	34	30	25	22.5	-	-	-	-	-	-
		UPSS-30A3-060	1088.5	791	448	293	218	173	139.5	104.5	87	78	66	62	-	-	-	-	-	-
	5kVA	UPSS-50A3-008	199	157.5	100.5	67.5	49	39	33	27	22	19	16	14.5	13	11.5	11	8	7	
		UPSS-50A3-030	469	386.5	265	186	136	105.5	86.5	69	58	52	47	43	40	35.5	34	30	23.5	
		UPSS-50A3-060	1188	962	639.5	440.5	321.5	251	208	167.5	138.5	121.5	107	95.5	86.5	76	71.5	58.5	52	

※ 下記は25℃環境下、初期値による参考値であり、数値を保証するものではありません。

※ 定格負荷力率(W÷VA)は0.8です。

※ 3筐体以上の増設をご希望の場合は別途御相談下さい。